


DIN 2463 D3/T3, auf Wunsch wärmebehandelt
kalibriert, V=1,0 Herstellungslänge ca. 6 m

Abmessung		kg/mtr.	W.-Nr. 1.4301	geschl. K 240/320 1.4301	W.-Nr. 14404	W.-Nr. 1.4571
6,0 x	1,0	0,125	x			x
8,0 x	1,0	0,175	x			x
	1,5	0,244	x			
10,0 x	1,0	0,225	x	x		x
	1,5	0,319	x			x
12,0 x	1,0	0,275	x			x
	1,5	0,394	x			x
	2,0	0,501	x			
13,0 x	1,0	0,300	x			
14,0 x	1,0	0,326	x			x
	1,5	0,470	x			
	2,0	0,601	x	x		
15,0 x	1,0	0,351	x			x
	1,5	0,507	x	x		x
	2,0	0,651	x			
16,0 x	1,0	0,376	x			
	1,5	0,545	x			x
	2,0	0,701	x	x		
17,2 x	1,5	0,625	x			
	2,0	0,761	x			
	2,3	0,858	x			x
18,0 x	1,0	0,426	x			
	1,5	0,620	x			x
	2,0	0,801	x			x
20,0 x	1,0	0,476	x			x
	1,5	0,695	x	x		x
	2,0	0,901	x	x		x
	3,0	1,277	x			
21,3 x	1,6	0,789	x			x
	2,0	0,967	x	x		x
	2,6	1,217	x			x
22,0 x	1,0	0,526	x			
	1,5	0,770	x			
	2,0	1,002	x	x		
23,0 x	1,5	0,808	x			

Weitere Qualitäten und Abmessungen aus Werksvorrat lieferbar, auch in geschliffener Ausführung
Nahtlose Rohre und Rohrzubehör auf Anfrage!

Rundrohr, geschweißt

- 34 -




DIN 2463 D3/T3, auf Wunsch wärmebehandelt
kalibriert, V=1,0 Herstellungslänge ca. 6 m

Abmessung		kg/mtr.	W.-Nr. 1.4301	geschl. K 240/320 1.4301	W.-Nr. 14404	W.-Nr. 1.4571
25,0 x	1,0	0,601	x			x
	1,5	0,883	x	x		x
25,0 x	2,0	1,152	x	x		x
	2,5	1,409	x			
26,9 x	1,6	1,014	x			x
	2,0	1,247	x	x		x
	2,6	1,582	x	x		x
28,0 x	1,0	0,676	x			
	1,5	0,995	x			x
	2,0	1,302	x			x
30,0 x	1,0	0,726	x			x
	1,5	1,070	x			
	2,0	1,402	x	x		x
	2,5	1,722	x			
	3,0	2,028	x			
32,0 x	1,0	0,776	x			
	1,5	1,146	x			
	2,0	1,502	x			
33,7 x	1,6	1,286	x			
	2,0	1,588	x	x		x
	2,6	2,025	x			x
	2,9	2,237	x			
	3,2	2,444	x			x
35,0 x	1,5	1,258	x			x
	2,0	1,653	x	x		
36,0 x	2,0	1,703	x			
38,0 x	1,0	0,926	x			
	1,5	1,371	x			
	2,0	1,803	x			x
	2,6	2,305	x			
40,0 x	1,0	0,977	x			
	1,5	1,446	x			
	2,0	1,903	x	x		x
	3,0	2,779	x			
42,4 x	2,0	2,023	x	x		x

Weitere Qualitäten und Abmessungen aus Werksvorrat lieferbar, auch in geschliffener Ausführung
Nahtlose Rohre und Rohrzubehör auf Anfrage!

Rundrohr, geschweißt



- 35 -


DIN 2463 D3/T3, auf Wunsch wärmebehandelt
kalibriert, V=1,0 Herstellungslänge ca. 6 m

Abmessung	kg/mtr.	W.-Nr. 1.4301	geschl. K 240/320 1.4301	W.-Nr. 14404	W.-Nr. 1.4571
	2,6	2,591	x		x
	3,2	3,141	x	x	x
44,5 x	1,5	1,615	x		
	2,0	2,128	x		x
	2,6	2,728	x		x
45,0 x	1,5	1,620	x		
48,3 x	1,5	1,871	x		
	2,0	2,319	x	x	x
	2,6	2,975	x	x	x
	3,2	3,614	x		x
	3,6	4,029	x		x
50,0 x	1,0	1,227	x		
	1,5	1,822	x		
	2,0	2,404	x		x
	2,0	2,454	x		
52,0 x	1,0	1,277	x		
	1,5	1,897	x		
	2,0	2,504	x		
53,0 x	1,5	1,934	x		x
54,0 x	2,0	2,604	x		x
55,0 x	1,5	2,010	x		
	2,0	2,650	x		
56,0 x	1,5	2,050	x		
57,0 x	2,0	2,754	x		
	3,0	3,929	x		
60,0 x	1,0	1,480	x		
	1,5	2,185	x		
60,3 x	2,0	2,920	x	x	x
	2,6	3,757	x		x
	2,9	4,168	x		x
	3,2	4,575	x		
	3,6	5,111	x		x
	3,9	5,530	x		
63,5 x	1,6	2,480	x		
65,0 x	2,0	3,150	x		

Weitere Qualitäten und Abmessungen aus Werksvorrat lieferbar, auch in geschliffener Ausführung
Nahtlose Rohre und Rohrzubehör auf Anfrage!

Rundrohr, geschweißt

- 36 -




DIN 2463 D3/T3, auf Wunsch wärmebehandelt
kalibriert, V=1,0 Herstellungslänge ca. 6 m

Abmessung		kg/mtr.	W.-Nr. 1.4301	geschl. K 240/320 1.4301	W.-Nr. 14404	W.-Nr. 1.4571
70,0 x	1,5	2,573	x			
	2,0	3,405	x			x
	3,0	5,033	x			
76,1 x	1,6	2,985	x			
	2,0	3,711	x			x
	2,6	4,785	x			x
	2,9	5,315	x			x
	3,6	6,535	x			x
80,0 x	1,5	2,948	x			
	2,0	3,906	x			
	4,0	7,620	x			
83,0 x	1,5	3,061	x			
84,0 x	2,0	4,107	x			x
85,0 x	2,0	4,157	x			x
88,9 x	2,0	4,352	x			x
	2,6	5,618	x			x
	3,0	6,557	x			
	3,2	6,867	x			x
	4,0	8,504	x			x
100,0 x	1,5	3,720	x			
101,6 x	2,0	4,988	x			
	3,0	7,407	x	x		
104,0 x	2,0	5,108	x			x
108,0 x	2,0	5,308	x			x
	3,0	7,888	x			x
	4,0	10,417	x			
114,3 x	2,0	5,624	x			x
	2,6	7,272	x			x
	2,9	8,089	x			
	3,0	8,361	x			x
	3,6	9,979	x			x
	4,0	11,048	x			x
129,0 x	2,0	6,360	x			x
133,0 x	4,0	12,921				
139,7 x	2,0	6,896	x			x

Weitere Qualitäten und Abmessungen aus Werksvorrat lieferbar, auch in geschliffener Ausführung
Nahtlose Rohre und Rohrzubehör auf Anfrage!

Rundrohr, geschweißt



- 37 -

DIN 2463 D3/T3, auf Wunsch wärmebehandelt
kalibriert, V=1,0 Herstellungslänge ca. 6 m

Abmessung	kg/mtr.	W.-Nr. 1.4301	geschl. K 240/320 1.4301	W.-Nr. 14404	W.-Nr. 1.4571
4,0	13,592	x			x
154,0 x	2,0	7,612	x		x
168,3 x	2,0	8,328	x		x
	2,6	10,788	x		x
	3,0	12,417	x		x
	4,0	16,456	x		
204,0 x	2,0	10,116	x		
219,1 x	2,0	10,872			x
	3,0	16,233	x		x

EHP



Weitere Qualitäten und Abmessungen aus Werksvorrat lieferbar, auch in geschliffener Ausführung
Nahtlose Rohre und Rohrzubehör auf Anfrage!



Notizen

